



# **Product Datasheet**

04 Recessed Spots Adjustable LED>The COB Square Spots

# 51106A/AL/W



6W COB LED recessed spot. br>
Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions




#### **Physical Specification**

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Square Spots
Order Code	51106A/AL/W
Colour	Aluminium
Material	Aluminium
Shape	Rectangular
Length	92mm
Width	92mm
Height	61mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	80mm

Indoor	Yes
Adjustable	1 Direction
lastrical Characteristics	
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	12V
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Brand	Citizen
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-9W
Power Factor	0,9
Constant Current	Yes
500mA	12-18
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~50°C
Housing Material	Plastic
Output Terminal	Cable
Brand	HEP
Illumination Data	
	200014
Colour Temperature	3000K
Colour Temperature  Lumen Output	475lm
Colour Temperature  Lumen Output  Light Efficiency	475lm 79,16lm/W
Colour Temperature  Lumen Output	475lm
Colour Temperature  Lumen Output  Light Efficiency	475lm 79,16lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	475lm 79,16lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	475lm 79,16lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	475lm 79,16lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	475lm  79,16lm/W  80  36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	475lm  79,16lm/W  80  36°  11,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	475lm  79,16lm/W  80  36°  11,5cm  9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	475lm  79,16lm/W  80  36°  11,5cm  9cm  11,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	475lm 79,16lm/W 80 36°  11,5cm 9cm 11,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton  Barcode	475lm 79,16lm/W 80 36° 11,5cm 9cm 11,5cm 20 5291889033295
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	475lm 79,16lm/W 80 36°  11,5cm 9cm 11,5cm

## Energy Label



### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

