



Product Datasheet

08 Downlights Adjustable LED>The COB Box Type Shop Range

51130/B/W



30W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Physical Specification

Item Group	08 Downlights Adjustable LED
Family	The COB Box Type Shop Range
Order Code	51130/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	185mm

Width	185mm
Height	105mm
Cutout Hole Width	160mm
Cutout Hole Length	160mm
Recessed Ceiling	Yes
Depth Required	125mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	35,5V
Safety Class	
Power(Watts)	27W
IP Rating	IP20
Light Source	LED built in


LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24,75-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Lumen Output	2600lm
Light Efficiency	86,67lm/W
CRI	80
Beam Angle	38°
Illumination Diagram	
Packing Info	
Box Length	20,5cm
Box Width	20,5cm
Box Height	12,5cm

 Pcs/Carton
 12

 Barcode
 5291889061137

 HS Code
 9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

