

08 Downlights Adjustable LED>The COB Square Downlights

## 51140B/W/C



40W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery






### Physical Specification


Item Group	08 Downlights Adjustable LED
Family	The COB Square Downlights
Order Code	51140B/W/C
Colour	White
Material	Die Cast
Shape	Rectangular
Length	188mm

Width	188mm
Height	138mm
Cutout Hole Width	170mm
Cutout Hole Length	170mm
Recessed Ceiling	Yes
Depth Required	160mm
Indoor	Yes
Adjustable	2 Directions


## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	37,3V
Safety Class	
Power(Watts)	37,3W
IP Rating	IP20
Light Source	LED built in

LED Type	COB
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24-40W
Power Factor	0,9
Constant Current	Yes
1000mA	24-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

#### Illumination Data

Colour Temperature	4000K
Lumen Output	3300lm
Light Efficiency	82,5lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	

#### Packing Info

Box Weight	2kg
Pcs/Carton	8
Barcode	5291889044796
HS Code	9405409900



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

