



# **Product Datasheet**

08 Downlights Adjustable LED>The COB Box Type Shop Range

51230/B/C



2x30W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



185mm



105mm

#### Gallery



#### **Physical Specification**

Item Group	08 Dow
Family	The CC
Order Code	51230/8
Colour	Black
Material	Alumini
Shape	Rectang
Length	350mm

wnlights Adjustable LED

OB Box Type Shop Range

/B/C

nium


ngular

η

Width	185mm
Height	105mm
Cutout Hole Width	320mm
Cutout Hole Length	160mm
Recessed Ceiling	Yes
Depth Required	125mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	2x35,5V
Safety Class	ŢIII>
Power(Watts)	2x27W
IP Rating	IP20
Light Source	LED built in

LED Type	COB
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24,75-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Temperature	4000K
Lumen Output	2x2700lm
Light Efficiency	90lm/W
CRI	80
Beam Angle	38°
Illumination Diagram	
Packing Info	
Pcs/Carton	6
Barcode	
	5291889061359
HS Code	5291889061359 9405409900

## Energy Label



### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

