

Product Datasheet

www.1-light.eu

51230/B/W

08 Downlights Adjustable LED>The COB Box Type Shop Range



2x30W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	350mm I 185mm 105mm

Gallery



Physical Specification

Item Group

08 Downlights Adjustable LED

Family

The COB Box Type Shop Range

Order Code	51230/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	350mm



Width	185mm
Height	105mm
Cutout Hole Width	320mm
Cutout Hole Length	160mm
Recessed Ceiling	Yes
Depth Required	125mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type

Constant Current

Input Current	750mA
Voltage	2x35,5V
Safety Class	
Power(Watts)	2x27W
IP Rating	IP20
Light Source	LED built in



LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24,75-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud


Illumination Data

Colour Temperature	3000K
Lumen Output	2x2600lm
Light Efficiency	86,67Im/W
CRI	80
Beam Angle	38°
Illumination Diagram	

Packing Info	
Pcs/Carton	6
Barcode	5291889061342
HS Code	9405409900



Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!



