



Product Datasheet

08 Downlights Adjustable LED>The COB Box Type Shop Range

51230/W/W



2x30W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions







105mm

Gallery



Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Shape	
Length	

08 Downlights Adjustable LED

The COB Box Type Shop Range

51230/W/W

White

Aluminium


Rectangular

350mm

Width	185mm
Height	105mm
Cutout Hole Width	320mm
Cutout Hole Length	160mm
Recessed Ceiling	Yes
Depth Required	125mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	2x35,5V
Safety Class	ŢIII>
Power(Watts)	2x27W
IP Rating	IP20
Light Source	LED built in

LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24,75-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Lumen Output	2x2600lm
Light Efficiency	86,67lm/W
CRI	80
CRI Beam Angle	80 38°
Beam Angle	
Beam Angle	
Beam Angle Illumination Diagram	
Beam Angle Illumination Diagram Packing Info	38°
Beam Angle Illumination Diagram Packing Info Pcs/Carton	38°

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

