



## **Product Datasheet**

10 Track Spots>Adjustable LED Linear Track Light

### 65024T/B/W



10X5W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.





















Dimensions



#### Related items



40003A/B

#### **Physical Specification**

10 Track Spots
Adjustable LED Linear Track Light
65024T/B/W
Black
Aluminium + Plastic
Rectangular
580mm

Width	60mm
Height	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction


#### **Electrical Characteristics**

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10x5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	96V
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
LED Type	
	COB
LED Brand	Bridgelux

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-50W
Power Factor	0,9
Constant Current	Yes
500mA	60-100V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Protection	Short Circuit Protection
Illumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	10x400lm
Colour Temperature  Lumen Output  Light Efficiency	10x400lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	10x400lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	10x400lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	10x400lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	10x400lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	10x400lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	10x400lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	10x400lm  80lm/W  80  30°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	10x400lm  80lm/W  80  30°  51,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	10x400lm  80lm/W  80  30°  51,5cm  9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	10x400lm  80lm/W  80  30°  51,5cm  9cm  13cm

#### Energy Label



#### Certification & Warranty

Warranty 2 Years

Weee Directive Yes

# switch to one light!

