



# **Product Datasheet**

10 Track Spots>Adjustable LED Linear Track Light

# 65026T/B/C



40W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.













#### Downloads









#### Dimensions



#### Related items







40003A/B


#### **Physical Specification**

Item Group	10 Track Spots
Family	Adjustable LED Linear Track Light
Order Code	65026T/B/C
Colour	Black
Material	Aluminium + Plastic
Shape	Rectangular
Length	500mm

Width	60mm
Height	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
_	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	450mA
Voltage	88V
Power(Watts)	39,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	29-50W
Power Factor	0,9
Constant Current	Yes
450mA	65-111V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Protection	Short Circuit Protection
Ilumination Data	
Colour Temperature	4000K
Colour Temperature  Lumen Output	3400lm
Colour Temperature  Lumen Output  Light Efficiency	3400lm 85lm/W
Colour Temperature  Lumen Output	3400lm
Colour Temperature  Lumen Output  Light Efficiency	3400lm 85lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	3400lm 85lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3400lm 85lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3400lm 85lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm 85lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm 85lm/W 80 100°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm 85lm/W 80 100°  51,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	3400lm 85lm/W 80 100°  51,5cm 9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	3400lm 85lm/W 80 100°  51,5cm 9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	3400lm 85lm/W 80 100° 51,5cm 9cm 13cm

## Energy Label



### Certification & Warranty

Warranty 2 Years
Weee Directive Yes

switch to one light!

