

Product Datasheet

www.1-light.eu

10 Track Spots>The COB Track Spot Range

65612NT/B/C



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items



40003A/B


Physical Specification

Item Group	10 Track Spots
Family	The COB Track Spot Range
Order Code	65612NT/B/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	123mm

Diameter	90mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	

50 Hz	
60 Hz	
Power(Watts) 25-30W	
Power Factor 0,9	
Constant Current Yes	
750mA 33-40V	
IP Rating IP20	
Safety Class	
Dimmable	
Housing Material Plastic	
Output Terminal Connector	
Brand Lifud	
Direct action	
Protection Short Circuit Protection	
Short Circuit Protection	
Ilumination Data	
Ilumination Data	
Ilumination Data	
Illumination Data Colour Temperature 4000K	
Illumination Data Colour Temperature 4000K Lumen Output 2500lm	
Colour Temperature	
Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80	
Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38°	
Colour Temperature 4000K Lumen Output 2500lm Light Efficiency 83,33lm/W CRI 80 Beam Angle 38° Illumination Diagram	
Colour Temperature	
Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm	
Colour Temperature	
Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width 4000K 2500Im 83,33Im/W 80 80 80 80 80 80 80 80 80 8	
Colour Temperature 4000K Lumen Output 2500lm Light Efficiency 83,33lm/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm Box Width 10cm	

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

