



Product Datasheet

10 Track Spots>The COB Track Spots

65628T/W/W



15W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Related items



40003A/W

Physical Specification

Item Group	10 Track Spots
Family	The COB Track Spots
Order Code	65628T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	132mm

Diameter	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current

Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	35V
Power(Watts)	14W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver



220-240V


Input Voltage

50 Hz	Yes
60 Hz	Yes
Power(Watts)	12-18W
Power Factor	0,9
Constant Current	Yes
400mA	30-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
	Short Circuit Protection
Protection	Short Circuit Protection
Protection Illumination Data	Short Gircuit Protection
	3000K
Illumination Data	
Illumination Data Colour Temperature	3000K
Illumination Data Colour Temperature Lumen Output	3000K 1095lm
Illumination Data Colour Temperature Lumen Output Light Efficiency	3000K 1095lm 73lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3000K 1095lm 73lm/W
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 1095lm 73lm/W 80
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 1095lm 73lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 1095lm 73lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3000K 1095lm 73lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3000K 1095lm 73lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3000K 1095lm 73lm/W 80 45° 20cm 11,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3000K 1095lm 73lm/W 80 45°

 Barcode
 5291889043904

 HS Code
 9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	30000hours
Weee Directive	Yes

switch to one light!

