

20 Garden & Underwater>The LED Bollards Range Die cast

67034/G/W



15W LED Bollard, IP54 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	20 Garden & Underwater
Family	The LED Bollards Range Die cast
Order Code	67034/G/W
Colour	Grey
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	850mm
Diameter	120mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

Gear

Built In

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

15W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

350mA

Voltage

40V

Power(Watts)

14W

IP Rating

IP54

Light Source

LED built in

LED Brand

Cree

Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

13-15W

Power Factor


0,9

Constant Current

Yes

350mA	37-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~55°C
Housing Material	Plastic
Output Terminal	Connector
Manufacturer	HEP
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	450lm
Light Efficiency	30lm/W
CRI	80
Beam Angle	50°
Illumination Diagram	

Packing Info

Box Length	88,5cm
Box Width	14,5cm
Box Height	14,5cm
Box Weight	4,2Kg
Pcs/Carton	4
Barcode	5291889039150
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty

2 Years

Average Lifetime

30000hours

Weee Directive

Yes

switch to
one light!

one
LIGHT

