



Product Datasheet

15 Plafo>The LED Plafo Outdoor Round

67280N/G/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280N/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
0.00	Delle la
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-16W
Power Factor	0,9
Constant Current	Yes
500mA	19-32V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
llumination Data	
Colour Temperature	3000K
	3000K 960lm
Colour Temperature	
Colour Temperature Lumen Output	960lm
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	960lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	960lm 60lm/W 80 27cm 27cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	960lm 60lm/W 80 27cm 27cm 8cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

