

20 Garden & Underwater>The LED Bollards Range Cone reflector

67410/AN/C



12W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	20 Garden & Underwater
Family	The LED Bollards Range Cone reflector
Order Code	67410/AN/C
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	800mm
Diameter	120mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating

8

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

12W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

250mA

Voltage

44V

Power(Watts)

11W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Edison

Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

Power(Watts)	9-12W
Power Factor	0,9
Constant Current	Yes
250mA	36-48V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Protection	Short Circuit

#### Illumination Data

Colour Temperature	4000K
Lumen Output	1000lm
Light Efficiency	83,33lm/W
CRI	80
Illumination Diagram	

#### Packing Info

Box Weight	3,45Kg
Pcs/Carton	2
Barcode	5291889051640
HS Code	9405409900

#### Energy Label



## Certification & Warranty

Warranty

3 Years

Average Lifetime

50000hours

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

