O_{LIGHT}

Product Datasheet

www.1-light.eu

7056A/C

21 Industrial & Floodlights>The Industrial LED Lights Die cast



LED industrial wall light with COB. High lumen output, IP65, for outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	115mm I 260mm I I I 300mm I I I

Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial LED Lights Die cast
Order Code	7056A/C
Colour	Black
Material	Die Cast
Diffuser Material	PC
Shape	Rectangular

Length	260mm
Width	300mm
Height	115mm
Surface Wall	Yes
Indoor	Yes



Outdoor	Yes
Adjustable	No
IK Rating	10

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	1400mA
Voltage	35V
Power(Watts)	49W
IP Rating	IP65
Light Source	LED built in

LED Type	SMD
LED Brand	Febik
Gear	
Gear Type	Led Driver
Input Voltage	100-240V




50 Hz	Yes
60 Hz	Yes
Power(Watts)	37,5-50W
Power Factor	0,9
Constant Current	Yes
1250mA	30-40V
IP Rating	IP20
Safety Class	

Illumination Data

Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	80lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	28,8cm
Box Width	16,2cm
Box Height	30,8cm
Box Weight	2,9Kg
Pcs/Carton	6
Barcode	5291889040866
HS Code	9405409900







Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to one light!



