



Product Datasheet

21 Industrial & Floodlights>The Industrial LED Lights Die cast

7056/C



LED industrial down light with COB LED. High lumen output, IP65, for outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Physical Specification

21 Industrial & Floodlights
The Industrial LED Lights Die cast
7056/C
Black
Die Cast
Rectangular
263mm
305mm
180mm
Yes
Yes
Yes


Outdoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1400mA
Voltage	35V
Power(Watts)	49W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes

60 Hz	Yes
Power(Watts)	34-50W
Power Factor	0,9
Constant Current	Yes
1400mA	24-36V
IP Rating	IP20
Safety Class	

Illumination Data	
Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	80lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info	
Box Length	28,8cm
Box Width	16,2cm
Box Height	30,8cm
Box Weight	2,9Kg
Pcs/Carton	4
Barcode	5291889045397
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty 3 Years
Weee Directive Yes



