

Product Datasheet

www.1-light.eu

7820V/C

09 LED Strips & Profiles>The Vertical Light Range 24V

CE



Vertical light Flexible LED light strip, with SMD3014 LEDs, 60LEDs/meter, 4,8W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions

Cut every 10cm (6-LED segment)												
-		-			-	_						8mm

Gallery

Downloads


IES

ŝ



Accessories









Related items



20030

Physical Specification

Item Group	09 LED Strips & Profiles		
Family	The Vertical Light Range 24V		
Order Code	7820V/C		
Shape	Rectangular		
Length	5m		
Width	8mm		
Surface Ceiling	Yes		
Surface Wall	Yes		
Surface Floor/Ground	Yes		
Indoor	Yes		

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	4,8W/m

IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3014
LED Brand	Refond
LED Number	60LEDS/m




Colour Temperature	4000K		
Lumen Output	500lm/m		
Light Efficiency	104,16lm/W		
CRI	90		
Illumination Diagram			

Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Pcs/Carton	40
Barcode	5291889059219
HS Code	9405409989

Energy Label





Warranty	5 Years		
Weee Directive	Yes		

switch to one light!



