



Product Datasheet

09 LED Strips & Profiles>The 19,2W/m Indoor 24V

7825/W



Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 19,2W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions

Cut every 5cm (7-LED segment)



Gallery



Physical Specification

Item Group	09 LED Strips & Profiles
Family	The 19,2W/m Indoor 24V
Order Code	7825/W
Shape	Rectangular
Length	5000mm
Width	10mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	19,2W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Refond
LED Number	140LEDs/m
F Mark	F

Ш	lumi	inati	ion	Data

Colour Temperature	3000K
Lumen Output	1536lm/m
Light Efficiency	80lm/W
CRI	90
Illumination Diagram	

Packing Info


Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,18kg

 Pcs/Carton
 40

 Barcode
 5291889045991

 HS Code
 9405409989

Energy Label



Certification & Warranty

Warranty 5 Years
Weee Directive Yes

switch to one light!

