



Product Datasheet

09 LED Strips & Profiles>The RGB & RGBW Strips

7830/RGBW



RGBW flexible LED light strip, with SMD5050 LEDs, 60LEDs/meter, 19,2W/meter. Supplied in 5 meters roll, with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions

Cut every 10cm (6-LED segment)

Related items



20036

Physical Specification

Item Group	09 LED Strips & Profiles
Family	The RGB & RGBW Strips
Order Code	7830/RGBW
Shape	Rectangular
Length	5m
Width	12mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Electrical Characteristics	

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	19,2W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5050
LED Brand	Refond
LED Number	60Leds/m

Illumination Data

Colour Temperature RGBW

Illumination Diagram

Packing Info

Box Weight	0,2kg
Pcs/Carton	40
Barcode	5291889048824
HS Code	9405409989

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes



