O_{LIGHT}

Product Datasheet

www.1-light.eu

09 LED Strips & Profiles>The Ultra Slim Range 24V

CE





Slim Flexible LED light strip, with SMD2110 LEDs, 196LEDs/meter, 14,4W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 3,5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.

Dimensions

Cut every 3,5cm (7-LED segment)

Gallery

ŝ

Downloads

IES



Related items



20030

Physical Specification

Item Group

09 LED Strips & Profiles



Family	The Ultra Slim Range 24V
Order Code	7833/C
Shape	Rectangular
Length	5m
Width	4mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	14,4W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2110
LED Brand	Refond
LED Number	196Leds/m

Illumination Data


Lumen Output	1300lm/m
Light Efficiency	90,28lm/W
CRI	90
Illumination Diagram	



Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Pcs/Carton	40
Barcode	5291889058816
HS Code	9405409989

Energy Label



Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to one light!



