

# **Product Datasheet**

www.1-light.eu

09 LED Strips & Profiles>The 230V IP65 Range

7860/W



230V Waterproof LED strip 9W/m, IP65.

Supplied in 50m rolls.

Can be cut every 1m.

Requires power supply order code 7860P.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



### Gallery



## Must be ordered separately



7860P

#### Accessories











C 7860E 7860F


7860L

7860R

Thysical openication	
Item Group	09 LED Strips & Profiles
Family	The 230V IP65 Range
Order Code	7860/W
Shape	Rectangular
Length	50000mm
Width	15mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Fitting + Driver Input Voltage	220-240V
	220-240V Yes
Input Voltage	
Input Voltage 50 Hz	Yes
Input Voltage 50 Hz 60 Hz	Yes
Input Voltage  50 Hz  60 Hz  Safety Class	Yes Yes
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)	Yes Yes  9W/m
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating	Yes Yes  9W/m  IP65
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source	Yes  Yes  9W/m  IP65  LED built in
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable	Yes  Yes  9W/m  IP65  LED built in  No
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable	Yes  Yes  9W/m  IP65  LED built in  No
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable  F Mark	Yes  Yes  9W/m  IP65  LED built in  No
Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable  F Mark  Fitting	Yes  Yes  9W/m  IP65  LED built in  No

Light Source	LED built in
LED Type	SMD 3528
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	450W
Power Factor	0,9
IP Rating	IP65
Safety Class	
Manufacturer	0
Protection	0
Illumination Data	
Colour Toron another	200014
Colour Temperature	3000K
Lumen Output	860lm/m
Light Efficiency	95,55lm/W
CRI	80
Illumination Diagram	
Packing Info	
Pcs/Carton	50
Barcode	5291889030928
HS Code	9405403990

# Energy Label



#### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



