



Product Datasheet

09 LED Strips & Profiles>The High Power Strips 24V

7880/C



Flexible LED light strip, with SMD2835 LEDs, 120LEDs/meter, 28,8W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (12-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions

Cut every 10cm (12-LED segment)



Gallery



Physical Specification

Item Group	09 LED Strips & Profiles
Family	The High Power Strips 24V
Order Code	7880/C
Shape	Rectangular
Length	5000mm
Width	20mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	ŢIII >
Power(Watts)	28,8W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Refond
LED Number	120LEDs/m
F Mark	F

Illumination Data

Colour Temperature	4000K
Lumen Output	2304lm/m
Light Efficiency	80lm/W
CRI	90
Illumination Diagram	

Packing Info


Box Length	24cm
Box Width	21,5cm
Box Height	3,5cm
Box Weight	0,365kg

 Pcs/Carton
 40

 Barcode
 5291889040446

 HS Code
 9405409989

Energy Label



Certification & Warranty

Warranty 5 Years

Weee Directive Yes

switch to one light!

