






ONE 60 DALI

Indoor LED recessed wall light, black, 3000/4000K

Do you want particularly pleasant, DALI dimmable light for your room in conjunction with an unusual design? This is exactly what the ONE luminaire family provides! Regardless of whether it is a wall light or a pendant, ONE will put every room is the right light. This surface-mounted wall light is sustainable and low-maintenance thanks to the anticipated service life of 30,000 hours.



TECHNICAL DATA

Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage 600 mA/V Diameter 60.0 cm Depth 8.0 cm Net weight 1.595 kg Gross weight 3.313 kg Safety class I Assembly Surface Assembly details Ceiling, Wall Dimmable Ja Dimming technology DALI Wattage 25.0 W Lumen 1500 Im CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature 50 °C	Item no.:	1002918
Diameter60.0 cmDepth8.0 cmNet weight1.595 kgGross weight3.313 kgSafety classIAssemblySurfaceAssembly detailsCeiling,WallDimmableJaDimming technologyDALIWattage25.0 WLumen1500 lmCRI>80Binning3Service life30000 hMinimum ambient temperature-20 °C	Primary nominal voltage	220-240V ~50/60Hz mA/V
Depth 8.0 cm Net weight 1.595 kg Gross weight 3.313 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimmable Ja Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Secondary power / secondary voltage	600 mA/V
Net weight Gross weight 3.313 kg Safety class I Assembly Surface Assembly details Ceiling,Wall Dimmable Ja Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Diameter	60.0 cm
Gross weight Safety class I Assembly Assembly details Ceiling,Wall Dimmable Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature	Depth	8.0 cm
Safety class Assembly Surface Ceiling,Wall Dimmable Dimming technology DALI Wattage 25.0 W Lumen 1500 Im CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature	Net weight	1.595 kg
Assembly Surface Assembly details Ceiling,Wall Dimmable Ja Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Gross weight	3.313 kg
Assembly details Ceiling,Wall Dimmable Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Safety class	I
Dimmable Ja Dimming technology DALI Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Assembly	Surface
Dimming technology DALI Wattage 25.0 W Lumen 1500 Im CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Assembly details	Ceiling, Wall
Wattage 25.0 W Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Dimmable	Ja
Lumen 1500 lm CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Dimming technology	DALI
CRI >80 Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Wattage	25.0 W
Binning 3 Service life 30000 h Minimum ambient temperature -20 °C	Lumen	1500 lm
Service life 30000 h Minimum ambient temperature -20 °C	CRI	>80
Minimum ambient temperature -20 °C	Binning	3
	Service life	30000 h
Maximum ambient temperature 50 °C	Minimum ambient temperature	-20 °C
	Maximum ambient temperature	50 °C
BIG WHITE Page 140	BIG WHITE Page	140

							1			-1			4		ч		ч	-1	1	7	7	7	7	7	7	ч									
	4	4	٠,	١,	١.	١.	ı	ı	J	4	J	J	J	J	a,	a	ä	J.																	
١.	1 1 1	L	. د	i,	1.	١.	ı	ı	u	ā	J	a.	J	ä	J	J		J			J		1		J	J	4	J.	J.	J.	١,	١,	L	4	
									а		ú	ä	J.	á	ā	ā	J.	J	J.	ä	ä	J.	ı	ı	ä	ä	á								



Notes				