




NOTAPO II

Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO II WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO II recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1002980
Secondary power / secondary voltage	700 mA/V
Width	3.6 cm
Height	18.0 cm
Depth	3.8 cm
Installation length	17.3 cm
Installation width	2.8 cm
Installation depth	5.0 cm
Net weight	0.105 kg
Gross weight	0.157 kg
Safety class	III
Assembly	Recessed
Assembly details	Wall, Wall with Acc.
Wattage	2.2 W
Lumen	6 lm
Colour temperature	3000 Kelvin
CRI	>90
Binning	6
LXXBXX data	L70B50
Service life	35000 h
Maximum ambient temperature	40 °C
BIG WHITE Page	440

Accessories

1002981	NOTAPO I and II WL installation frame
464142	LED DRIVER , 10.5W, 700mA, incl. strain relief, dimmable
464200	LED DRIVER , 3W, 700mA, incl. strain relief

Notes
