




## DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP67, stainless steel 316, 230V, 6W

The surface-mounted DASAR PROJECTOR series lights are fitted with a 6W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP67 protection class, the luminaire is suitable for outdoor use. The stainless steel DASAR PROJECTOR series includes a further aluminium version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. The lamps in the luminaire cannot be replaced.



## **TECHNICAL DATA**

Item no.:	233571
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	400 mA/V
Vertical tilting range	90 °
Length	7.2 cm
Width	10.0 cm
Height	10.8 cm
Net weight	1.418 kg
Gross weight	1.505 kg
IP Code	IP 67
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc., Ground, Ground with Acc., Wall, Wall with Acc.
Wattage	5.5 W
Lumen	300 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
CRI	>80
Binning	6
Service life	25000 h
BIG WHITE Page	598

					-				-			-		-		-	-	-	-	-	-	-	-	-									
- 4	4	- 4	a,	J	J	J	4	a	J	J	ı	J	J	4	4	4	a,																
	L I	ı,	1	J	J	J	J	4	J	J	J	J	J	J	J		4		4		1		4	4	1	ı	ı	ı	1	J,	۱.	1 .	ı
											- 4	- 4																					



## Accessories

233580	EARTH SPIKE , for DASAR PROJECT- OR, stainless steel 316
233581	INSTALLATION PLATE , for DASAR PROJECTOR outdoor floodlight, anodised aluminium
233582	INSTALLATION PLATE , for DASAR PROJECTOR outdoor floodlight, stainless steel 316
900011	PLASTIC EARTH SPIKE , black, length 17.5cm

Notes		