

## Product data sheet – Gas range with 2 burners, Town gas operated

MKN-No.:  
2063413

Range according to DIN 18851 for all-purpose application in commercial kitchens. For the preparation of dishes in saucepans and pans on one surface. For boiling, steaming, frying, braising, simmering and steam frying.



## Technical highlights

### Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.  
Visible surfaces with polished and satin finish, 320 grit.

### Bendings:

Cover bent downwards 50 mm at the front and on the sides, bent upwards 25 mm at the rear. Designed as a drip edge at the front on the bottom side. 50 mm cover projection closed to the appliance body. With tightly welded drain channels on the side – rounded (R30) at the rear.

### Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

### Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Ergonomically shaped knobs for a easy identification of the position.

### Effective area:

CNS/stainless steel hob with large radii, easy to clean, seamlessly and tightly deep drawn 70 mm to the cover plate. The burners which are sealed downwards have atmospheric burner heads. Removable sliding grid 350 x 700 mm of CNS/stainless steel (for two burners).

### Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

### Type of energy:

Appliance is completely tubed internally in accordance with gas requirements for the gas connection provided by customer.

### Special feature:

### Heating:

Heating by atmospheric burner heads, thermoelectrically protected. Ignition burner and thermoelement protected by a removable cap. Nozzle and primary air aperture of the ignition burner protected under the hob. The heating power setting occurs by means of a thermoelectrically protected multi-gas tap for each cooking zone. Gas cut off cock integrated in the panel.

## Product data sheet – Gas range with 2 burners, Town gas operated

MKN-No.:  
2063413

Range for the preparation of dishes in saucepans and pans on one surface. For boiling, steaming, frying, braising, simmering and steam frying.

### Further features

- connection, sealing by special clip bars flush mounted to the cover (optional)

### Technical data

|   |                 |
|---|-----------------|
| Dimensions (LxWxH*) (mm):                             | 400 x 850 x 700 |
| Effective area:                                       | 2               |
| Dim.: effect. area (LxWxH) (mm):                      | x x 70          |
| Diameter (mm):  |                 |
| Nominal capacity (L):                                 |                 |
| Nominal fill quantity (L):                            |                 |
| Connected load (electrical) (kW):                     |                 |
| Voltage <sup>1</sup> (V):                             |                 |
| Recommended fuses (A):                                |                 |
| Frequency range (Hz):                                 | 50/60           |
| Rated heat load (kW):                                 | 10,5            |
| Standard gas pressure – town gas <sup>2</sup> (mbar): |                 |
| Gas connection:                                       | DN 20 (3/4")    |
| Heat-up time (Min.):                                  |                 |
| Vapour pressure (bar):                                |                 |
| Refrigeration capacity (kW):                          |                 |
| Net weight (kg):                                      | 47              |
| Gross weight <sup>3</sup> (kg):                       | 54              |
| Heat emission latent (W):                             | 1050            |
| Heat emission sensitive (W):                          | 2625            |
| Type of protection:                                   |                 |

\* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

### Product safety

- CE mark

### Installation requirements

- gas connection provided by customer

### Option / accessories

| MKN-No.: | Description:                                |
|----------|---|
| 201861   | solid plate to cover for one C-burner       |
| 206007   | CNS grid to cover 1 burner                  |
| 845031   | wing door for an appliance length of 400 mm |
| 204352   | 1 set appliance foot, 150 mm high (4pcs)    |
| 204252   | 1 set appliance foot, 200 mm high (4pcs)    |

<sup>1</sup> special voltages on request

<sup>2</sup> further types of gas on request

<sup>3</sup> seaworthy packing on request

