

POWER PRIMER

SURFACE TREATMENT



Safety Datasheet March 2023

V1.1 M130

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Power Primer
Product type/use: Cleaner
Restriction of Use: None identified
Company address: Redtronic Limited
Units 1-10 Wellington Business Park
Quebec Street, Eland, HX5 9BX

Region: United Kingdom
Contact information:
Telephone: +44 01422 310999

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
2-Propanol	67-63-0	80 - 100
Titanium tetrabutanolate	5593-70-4	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting. Rinse the mouth. Drink 1-2 glasses of water.

Symptoms: See Section 11.

Notes to physician: This material, if aspirated into the lungs, may cause lipid pneumonitis. Treat affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical, or carbon dioxide. Water Sand.

Special firefighting procedures: Wear self-contained breathing apparatus. Wear full protective clothing.

Unusual fire or explosion hazards: DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions.

Hazardous combustion products: Irritating and toxic gases or fumes may be released during a fire. Carbon oxides.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area, and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. Remove all sources of ignition.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to local governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin, and clothing. Do not inhale vapors and fumes. Do not take internally. For industrial use only. Keep away from heat, spark, and flame.

Storage: For safe storage, store between 5.0 °C (41°F) and 40.0 °C (104°F)
Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m ³) PEL	None	None
Titanium tetrabutanolate	None	None	None	None

Engineering controls:	Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.
Respiratory protection:	If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.
Eye/face protection:	Wear safety glasses; chemical goggles (if splashing is possible).
Skin protection:	Wear impervious gloves for prolonged contact. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Clear
Odor:	Alcohol
Odor threshold:	Not available.
pH:	5 - 6
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	0.7900 at 20.00 °C (68°F)
Vapor density:	Not available.
Flash point:	12.00 °C (53.6 °F) no method
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Miscible
Partition coefficient (n-octanol/water):	Not available.
VOC content:	98 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	Reaction with strong oxidants.
Reactivity:	Not available.

11. TOXICOLOGICAL INFORMATION

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.
 Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: This product may cause slight irritation to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea, and incoordination.
 Skin contact: Prolonged or repeated skin contact may result in redness, burning sensation or dermatitis.
 Eye contact: Causes serious eye irritation. This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
 Ingestion: Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Titanium tetrabutanolate	Oral LD50 (Rat) = 3,122 mg/kg Oral LD50 (Rat) = 3,122 mg/kg	Irritant, Eyes

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	No	No
Titanium tetrabutanolate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local governmental regulations for disposal.

OTHER INFORMATION

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Redtronic limited does not assume responsibility for any results obtained by persons over whose methods Redtronic has no control. It is the user's responsibility to determine the suitability of Redtronic products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Redtronic's products. In light of the foregoing, Redtronic specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Redtronic's products. Redtronic further disclaims any liability for consequential or incidental damages of any kind, including lost profits.