

LIGHTBARS

<u>BEACONS</u>

MINIBARS

DIRECTIONALS

WORKLAMPS

SIRENS

SPEAKERS

SWITCHES

AUXILIARY





TornadoXS

Beacon and Speaker/Siren Combination









Redtronic's TornadoXS (TXS) is a combination beacon, siren & speaker system designed for temporary mount applications (primarily magnetic). Any vehicle can instantly become an emergency response vehicle whilst meeting all regulatory standards required for public road use. The TXS is also perfect for users not wanting to make permanent installations to their vehicle.

The TornadoXS incorporates the immensely popular low-profile Tornado B47 beacon (with a blue lens as standard) with a S2OIS digital siren & speaker within a compact and robust enclosure.

As standard the TXS is supplied with a multifunctional cigarette plug. For users requiring enhanced functionality there is also a model which includes a inline LINX4 universal controller.

The user can programme the desired siren tone from 10 countries and 27 tone variants by following a programming sequence using the inbuilt programming port.

The TXS is designed for the toughest environments and is approved to EMC UNECE R10, UNECE R65, UTAC and comes with 7 standard flash patterns including ICAO/CAP168 airport pattern. The TornadoXS is manufactured in the UK and is endorsed with a 3 year warranty.

PART NUMBER	COLOUR	TYPE	VOLTAGE	WARRANTY
XT1M-047-BBLL		LATCH-LATCH CIGARETTE PLUG	10-30V	3 YEARS
XT1M-047-BBLM		LATCH-MOMENTARY CIGARETTE PLUG	10-30V	3 YEARS
XT1M-047-BBL4		LINX4 (3 TONES)	10-30V	3 YEARS

FEATURES AND BENEFITS

- · Wide-angle FX Optic with Ultra-bright latest generation LED's
- · UV stabilised polycarbonate lens
- · Lens colours: Blue
- · R65 Class II approved (Blue)
- · EMC R10 compliant
- · IP45 (main unit), IP69K (beacon), IP69K (speaker)
- · Magnetic Mount
- · 20w Neodymium speaker
- · Inbuilt 20w digital siren
- 7 flash patterns
- · CAP168/ICAO airport flash
- · Night and day (dim mode)
- · Light weight design
- Multi-function cigarette plug or LINX4 Universal controller options
- Voltage: 10-30VDC
- · Synchronisation with other Redtronic products
- · Warranty: 3 years

DIMENSIONS











