

LIGHTBARS

BEACONS

MINIBARS

DIRECTIONALS

WORKLAMPS

SIRENS

SPEAKERS

SWITCHES

AUXILIARY





Tornado-X Duo


Beacon and Speaker/Siren Combination











The TornadoX Duo incorporates the immensely popular low-profile Tornado B47 beacon (with a blue lens as standard) with 2x S20IS digital siren & speakers within a compact and robust enclosure.

As standard the TXD is supplied with a multifunctional cigarette plug. For users requiring enhanced functionality there is also a model which includes a inline LINX4 universal controller.

The TornadoX Duo is likely the most stringently tested product Redtronic offer, mainly due to the German KBA testing and approval which incorporates a brake test to ensure the magnets reliably remain in place in case of a collision or harsh braking. The decibel output of the sirens & speakers have also been tested to the highest KBA standard to optimise the system performance.

The user can programme the desired siren tone from 9 countries and 26 tone variants by following a programming sequence using the inbuilt programming port.

The TXD is designed for the toughest environments and is approved to EMC UNECE R10, UNECE R65, KBA, UTAC and comes with 7 standard flash patterns including ICAO/CAP168 airport pattern. The TornadoX Duo is manufactured in the UK and is endorsed with a 3 year warranty.

PART NUMBER	COLOUR	TYPE	VOLTAGE	WARRANTY
XT2M-047-BBLL1		LATCH-LATCH CIGARETTE PLUG	10-30V	3 YEARS
XT2M-047-BBLM1		LATCH-MOMENTARY CIGARETTE PLUG	10-30V	3 YEARS
XT2M-047-BBL41		LINX4 (3 TONES)	10-30V	3 YEARS

FEATURES AND BENEFITS

- Wide-angle FX Optic with Ultra-bright latest generation LED's
- UV stabilised polycarbonate lens
- Lens colours: Blue
- R65 Class II approved (Blue)
- **EMC R10 compliant**
- IP65 (main unit), IP69K (beacon), IP69K (speaker)
- Magnetic Mount
- 2x 20w Neodymium speaker
- 2x Inbuilt 20w digital siren
- 7 flash patterns
- **KBA Brake Tested magnet mount**
- CAP168/ICAO airport flash
- Night and day (dim mode)
- Light weight design
- Multi-function cigarette plug or LINX4 Universal controller options
- Voltage: 10-30VDC
- Synchronisation with other Redtronic products
- Warranty: 3 years

DIMENSIONS

