



LIGHTBARS

BEACONS

MINIBARS

DIRECTIONALS

WORKLAMPS

SIRENS

SPEAKERS

SWITCHES

AUXILIARY



MANUFACTURED IN THE
UNITED KINGDOM



TORNADO
B150

Tornado B150 Beacons

Redtronic's Tornado B150 beacon is designed to incorporate a sleek design in the tallest profile of the Tornado beacon range whilst providing the ultimate light output to meet R65 Class I amber and Class II blue. The Tornado B150 beacon meets IP69K to protect against water and dust and features include CAP168/ICAO approval, multiple flash patterns and a variety of mounting options to meet most vehicle fitting needs. Contributing to the vast features and approvals of the Tornado B150 beacon include CISPR25 Level 3 and as standard built in auto dim sensor. It features ultra-bright latest generation LEDs under an ultra-strong UV stabilised polycarbonate lens offering multiple lens colour options and LED colours. The Tornado B150 beacon is tough enough for any job and that is why it has been designed for a fit-and-forget purpose and has a 3-year warranty.

Part Number	LED Colour	Lens Colour	Voltage	Mount	Warranty
BTN3-150-AC			11-32VDC	3 Bolt	3 years
BTN3-150-AA			11-32VDC	3 Bolt	3 years
BTN3-150-BC			11-32VDC	3 Bolt	3 years
BTN3-150-BB			11-32VDC	3 Bolt	3 years
BTN1-150-AC			11-32VDC	1 Bolt	3 years
BTN1-150-AA			11-32VDC	1 Bolt	3 years
BTN1-150-BC			11-32VDC	1 Bolt	3 years
BTN1-150-BB			11-32VDC	1 Bolt	3 years
BTNM-150-AC			11-32VDC	Magnetic	3 years
BTNM-150-AA			11-32VDC	Magnetic	3 years
BTNM-150-BC			11-32VDC	Magnetic	3 years
BTNM-150-BB			11-32VDC	Magnetic	3 years
BTNF-150-AC			11-32VDC	Flexi DIN	3 years
BTNF-150-AA			11-32VDC	Flexi DIN	3 years
BTNF-150-BC			11-32VDC	Flexi DIN	3 years
BTNF-150-BB			11-32VDC	Flexi DIN	3 years

Features and Benefits

- Ultra-bright latest generation LED's
- Ultra-strong UV stabilised polycarbonate lens
- Synchronisation capability with other Redtronic products
- Dekra Speed Rating: 146.6mph (236.2km/h) mag mount
- Operating Temperature: -40 to +105°C
- Multiple mount options available
- R65 Class II approved (blue) Class I (amber)
- IP69K protection against dust & water ingress
- CISPR 25 level 3 and CAP168/ICAO airport flash
- EMC R10 compliant
- Auto DIM (night & day) and Cruise feature available
- 11-32VDC operation
- 9 flash patterns
- Multi-function cigarette plug (mag mount)
- 3 year warranty



Dimensions

