

TOP AIR[®] ATV SPRAYER

200-GALLON

GO WHEN AND WHERE BIG SPRAYERS CAN'T



60' boom



45' Boom

60' Boom





ATV SPRAYER FEATURES AND BENEFITS

- Self-leveling, 30', 45' or 60' manual front-fold booms and tongue-mounted shock absorber system ensure uniform spraying over uneven terrain
- Boom breakaway feature allows the boom to spring backward should it hit an obstruction and quickly return to operating position
- Tool-free height-adjustable boom from 12" to 30" with standard-equipment winch and locks securely in place
- Self-leveling tongue and standard 1 7/8" ball hitch for easy hookup and jack for easy storage
- In-line boom strainer virtually eliminates nozzle plugging for uniform spraying and 2" quickfill for fast loading
- Three-section boom with electronic ball valves and single-tip nozzles available on 15" or 20" spacings and an easy-to-see pressure gauge mounted at the front of the unit for handling a wide variety of spraying applications
- Standard tank agitation for keeping contents properly suspended and highly visible tank volume indicator
- Tandem axles are infinitely adjustable from 60" to 90" to match row widths
- Standard 24x10.5-10 high-flotation tires can be moved fore and aft to ideally distribute weight
- Units are finished with a baked-on powder-coat finish for corrosion resistance
- 5.5 HP Honda motor-driven centrifugal pump for easy and reliable operation
- 9-gallon clean water tank with spout and eye wash tube is also equipped with a storage container
- Optional factory-installed accessories include a foam marker system with two 3 1/2-gallon tanks, fence row nozzle kit for precision spray placement, rate controller options, spray gun kit with 25' of hose and transport light kit

With big sprayer performance in a small package, the ATV sprayer is a unit that can quickly pay for itself. See your nearest dealer today for a close-up look at all the Top Air sprayers or visit us online at www.topairequip.com.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
419-532-3121


®™ Trademarks, registered or applied for,
of Unverferth Manufacturing Co., Inc., Kalida, OH



© 2019
ATV9151000M5



Fill Level Gauge



Hose Reel

SPECIFICATIONS

	30'/45' boom	60' boom
ATV Requirements	600cc min.	
Ground clearance	18"	
Transport height	7'8"	6'4"
Transport width	8'6"	9'10"
Transport length	13'10"	
Weight	1,400 lbs	1,950 lbs

As we continually strive to improve our products, all specifications contained herein are subject to change without notice or obligation.