

HOW TO INSTALL THE FJ CRUIDER FIRE EXTINGUISHER BRACKET

- (1) Using a 10mm socket, remove the bolt from each of the grocery bag hangers which are located on the driver's side of the rear cargo area. Note: the bag hangers will drop out when the bolts are removed.
- (2) Install the 2 longer replacement bolts in the holes located in the Fire Extinguisher Bracket.
- (3) On the back side of the bracket, over each bolt, slide a white spacer then a bag hanger. Note: the bag hanger has a hole similar in size to the spacer.
- (4) Position the bag hanger so that the pins on the back are in horizontal alignment with the holes into which they will be placed.
- (5) With the bracket facing to the front (marked), carefully push the assembly into position.
- (6) Hand tighten the 2 bolts until the bracket is properly aligned.
- (7) Tighten the bolts to 40 INCH POUNDS using a 10mm socket. Note: do not over tighten as the bolt hole threads may strip.
- (8) Install a properly sized Fire Extinguisher and engage the hold down strap.

NOTE: This Fire Extinguisher Bracket was designed to hold a standard 2 1/2# sized Fire Extinguisher such as those sold by Kidde. If you are having difficulty or are uncomfortable installing our Fire Extinguisher Bracket, please call us for assistance.

REPACKBOX
P.O. BOX 263
PEGRAM, TN 37143
info@repackbox.com