



WOCA WOODCARE

📞 877-962-2645 ✉ info@wocawoodcare.com

WOCA DIAMOND OIL ACTIVE APPLICATION INSTRUCTIONS

WOCA Diamond Oil ACTIVE is a high quality, premium one component oil that provides an extremely durable dirt and water repellent surface. Can be used on all wood species of wood flooring and woodwork. Suitable for residential and commercial projects.

Product Instructions:

1. The unfinished flooring or woodwork must be sanded to grit 120-150 and be clean and dry. Minimum room temperature during application should be 60 degrees.
2. Mop floor with WOCA Intensive Wood Cleaner and let dry completely (see separate Intensive Wood Cleaner instructions).
3. Shake oil container well before and during use. Containers with different batch numbers should be mixed before use to prevent potential color differences. Using a paint tray and paint roller, apply an even coat of oil on approx. 50-100 sq.ft. of flooring. For edges and corners use paint brush.
4. Leave the oil to absorb for 10-15 minutes. If dry spots appear, apply more oil.
5. Polish the area with a floor machine and white pad until floor appears saturated.
6. Polish off all excess oil from floor using cotton cloths under the pad. Hand wipe all edges and corners. No excess oil should be left on the surface.
7. If superior durability is desired, apply 3 oz of Diamond Oil Active per 100 sf within 6-12 hours of the first application. The oil should be polished thoroughly, as described in step 5 and 6.
8. The floor can be used with care after 24 hours. Do not expose treated area to water during hardening time, approx. 3-5 days.
9. After 5-7 days, clean floor with WOCA Natural Soap or Oil Refresher for additional protection.

Tip: For fastest drying time, leave windows slightly open to ensure a steady flow of fresh oxygen.

Warning! Rags, pads or waste soaked with WOCA oil may self-ignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for proper disposal.