CARTOP & SWITCHES



CARTOP STATION

With LED Flood Light



The Giovenzana Top of Car Inspection Station with adjustable LED Flood Light is designed for safe operation of an elevator car while performing inspections and maintenance.

It features a NO Neutral position Inspection switch, without margin of error in the switch, UP/DOWN car control buttons, ON/OFF light switch, Emergency Stop Button with guards, 2 - 120V GFCI outlets, seismic status with alarm, and fire service button.

The enclosure is made from a high impact thermoplastic material in a highly visible yellow.

Cartop Station Specifications

| Color: | Yellow |
|-------------------------|---|
| Connection Type: | Screw Terminals |
| Contact Rating: | 16 A @ 600Vac |
| Dimensions (L x W x H): | 360.08x317.1x118 mm (14.176x12.484x4.646") |
| Operating Temperature: | -25° - +70°C |
| Protection Type: | IP65 |
| Wire Connection Type: | Spring Clamp |
| Delco SKU: | A-GMS312 |

Features

- Yellow High Visibility Housing
- Knockouts For Easy To Add Wiring ports
- cCSAus certified
- High Impact Polycarbonate Enclosure
- Failsafe Normal to Inspection cam switch

Options

- LED Flood Light
- Incandescent bulb
- No light

CARTOP & SWITCHES



RUN STATION

Temporary Run Station with Tubular key lock



| Color: | Yellow |
|-------------------------|------------------|
| Contact Configuration: | 4 NO/1 NC |
| Contact Rating: | 16 A @ 600Vac |
| Dimensions (L x W x H): | 345x81x68 mm |
| Emergency Stop Button: | Yes |
| Housing: | Single Row |
| Motor Control Speed: | Single |
| Number of Operators: | 5 |
| Protection Type: | NEMA 4X and IP65 |
| Delco SKU: | A-PLO5MT-TUBKEY |

E-STOP

Emergency Stop Button with Visual Indicator



| Color: | Red/Yellow |
|-------------------------------|------------------|
| Contact Configuration: | 1NO/1NC |
| Contact Rating: | 16 A @ 600Vac |
| Dimensions (L x W x H): | 75x75x87.1 mm |
| Emergency Stop Button: | Yes |
| Housing: | E-Stop Enclosure |
| Motor Control Speed: | Single |
| Number of Operators: | 1 |
| Operator Type: | Push-Pull |
| Protection Type: | IP65 |
| Delco SKU: | A-SLA11NPNC001 |

CARTOP & SWITCHES



LIMIT SWITCH

With Adjustable Ø50 rubber roller lever



| Contact Type: | W02 - 2NC SLow Action Z11- 1NC/1NO Snap Action |
|---------------------|---|
| Cable Entry: | M20 |
| Max Current (A) | 10 Amps |
| Max Voltage (V): | 600 Vac |
| Protection Type: | IP67 |
| Switch/Button Type: | Limit Switch |
| Electrical Life: | >150,000 cycles |
| Mechanical Life: | >10 million cycles |
| Protection Type: | IP65 |
| Delco SKU: | A-FTNG140-W02 A-FTNG140-Z11 |

SAFETY SWITCH

Pull Out Safety Limit Swith Flat Key



| Contact Type: | 2NC/1NO Slow Action |
|---------------------|---------------------|
| Cable Entry: | M16 |
| Current Rating (A): | 10 A |
| Key Type: | Flat Key |
| Max Voltage (V): | 600 Vac |
| Protection Type: | IP67 |
| Switch/Button Type: | Safety Limit Switch |
| Electrical Life: | >150,000 cycles |
| Mechanical Life: | >10 million cycles |
| Protection Type: | IP65 |
| Delco SKU: | A-STNK02-W12 |