

# DOOR DETECTOR

Weco Door Detectors for 24V and 120V



Weco Door Detectors are easily installed and competitively priced.

The P profile is the leading product in the North American market. It is meant for large and heavy doors that have a clutch in the middle of the panel.

It was designed for GAL type doors with heavy duty construction and a full-length box section. It is suitable for wall mounting in elevators without car doors and can be installed in static and dynamic locations.

Every package includes a set of door detectors with travelling cables, power supply, mounting accessories and installation manual.

## Specifications

- True Travelling Cables with Plug In Connectors
- Anti Sunlight Function
- Special Model for Both side-opening and Center-Opening doors, with or without Nudging
- 11mm x 27.5mm x 2000mm
- 94 Non-Parallel Infra-Red Beams
- 32 Pairs of Diodes
- 3 Way Scan Mode
- 65ms Response Time
- 59mm Diode Spacing
- 0-3000mm (Max. 4000mm as required) Operating Range
- 20mm-1841mm Detecting Height
- 1:2 Infra-Red Pulses Ratio
- > 100,000LUX Max. Ambient Light (sunlight)
- 15mm Vertical, 4mm Horizontal Linear Tolerance
- 2 x 3,500mm Connection Flexible Cables
- Normal-Interrupted-Faulty System Indicators
- 1 x Yellow LED, 1 x Red LED
- -20°C – 65°C Operating Temperature Range
- -40°C – 85°C Storage Temperature Range
- IP51 (IP54 as required)
- > 1500V Isolation

Model	120VAC	24V
Delco SKU	B-23-16-0120	B-23-16-0026

We also carry replacement cables and power supplies.