

SPECIALIST|PRO

Electrosurgical Generator



The Bovie® Specialist Pro is the electrosurgery solution for in demand physician offices and specialty facilities. Designed to operate like an operating room generator in a compact lower watt package. The multipurpose unit is ideal for monopolar and bipolar office surgical procedures.

The Specialist|PRO offers 5 common energy outputs controlled by the new sleek, push-button design, with up to 120 watts of power. The modalities include Cut, Blend, Coagulation, Fulguration and Standard Bipolar.

Industry-standard connections allow for use of a variety of monopolar and bipolar accessories providing energy versatility across a variety of specialties such as OBGYN, Urology, Plastic Surgery, Dermatology, ER and more.

Bovie NEM™ neutral electrode monitoring increases patient safety by ensuring proper pad connectivity during procedures.

The Bovie Specialist|PRO is backed by the unmatched **4-year manufacturer warranty,** offered only by Bovie.

Efficiency, Versatility, and Safety ... Designed benefits for you and your patients



BOVIE® SPECIALIST PRO ELECTROSURGICAL GENERATOR



STANDARD EQUIPMENT

A1250S electrosurgical generator, **ESP1** sterile disposable pencil ES01 blade, ES02 needle, ES20 ball (1 each) sterile disposable electrodes ESRE (5) split disposable return electrode A1252C (2) reusable grounding cords 110 VAC Hospital-grade power cord* 220 VAC Hospital-grade power cord* User's guide (MC-55-237-001)*

* Not Pictured









ESRE

COMPLEMENTARY PRODUCTS †



SE02 Smoke Evacuator †



BV-1253B Monopolar Footswitch †



A1255A Footswitch Adapter †





Return Electrode with cord †



Disposable SuperCut[™] Needles Electrodes †



Disposable Resistick II™ Electrodes †



Disposable Dermal Loops †

[†] Sold Separately

PRODUCT SPECIFICATIONS

DIMENSIONS

Height: 15.2cm (6 in.) Width: 26cm (10.25 in.) Depth: 30.5cm (12 in.) Weight: < 4Kg (< 9 lbs.)

OUTPUT POWER

Cut: 120 watts Blend: 90 watts (60% Cut, 40% Coag)

Coagulation: 80 watts Fulguration: 40 watts Bipolar: 30 watts

OUTPUT FREQUENCY

350 - 600 kHz

LINE VOLTAGE

A1250S: 100-240 VAC

LINE FREQUENCY

50 - 60 Hz

WARRANTY

Four Years

