HiFlo2 Max HIGH SUCTION MOBILE PUMP

Clements HiFlo2 Max suction pumps feature advanced oil-less twin piston pump technology and have been designed for all high suction, high flow applications.

Virtually maintenance free, these units represent the ultimate in affordable and reliable mobile suction.

- Vacuum up to -90 kPa [-675 mmHg]
- Flow rate up to 90 litre/minute
- Quiet continuous operation (46.4 dBA)
- Footswitch is standard, with selectable instantaneous and maintained modes
- Electronic jar changeover
 (No increase in vacuum pulldown time as experienced with series connected jars)
- 3 stage overflow protection
- Dual scale vacuum indication kPa and mmHg
- Stable mobility, 4 x dual-track castors, 2 with brakes
- Minimal maintenance and easy to clean
- Shatter-resistant polycarbonate collection canisters
- Adaptable for use with disposable liner canisters
- Service kits and spare parts available

Supplied ready to use with 2 x 2L reusable jars, 2 x trap jars, jar brackets, 2 x suction tubing sets, 2 x filters and foot switch







HIFLO2 MAX MOBILE SUCTION PUMP

SPECIFICATIONS			
	HiFlo2 Max		
	SUC84604		
Power Rating	220 - 240 V 50/60 Hz 380W		
Maximum Vacuum	-90 kPa [-675 mm Hg]		
Maximum Flow Rate (free air)	90 litre/min		
Maximum Flow Rate (through jar)	80 litre/min		
Noise Level	46.4 dBA		
Operation Mode	Continuous operation		
Gauge	63 mm diameter, Bourdon tube type, dual scale, graduated in kPa and mmHg		
Gauge Range	0 to -100 kPa graduated at 5 kPa 0 to -760 mmHg graduated at 20 mmHg		
Vacuum Regulator	Needle valve type		
Pump Type	Twin piston, oil free		
Motor	Permanent split capacitor		
Foot Switch (included)	Dual Mode Footswitch (Instantaneous and Maintained)		
Electronic Jar Changeover	Electronic Jar Selection (Selectable from control panel for minimal disruption)		
	No increase in vacuum pulldown time as experienced with series connected jars		
Housing	Smooth Easy-Clean ABS		
Filter	Disposable Hydrophic and Antibacterial, 0.3 micron		
Collection Canister Reusable (included)	2 x 2 litre autoclavable, shatterproof polycarbonate jar, screw lid with integrated handle		
Overflow Protection	Positive Shut-off Float Valve in External Trap Jar		
Collection Canister	2 x 3 litre disposable liner system		
Disposable Liner (Option)	(Requires optional matching support jar and ring bracket)		
Overflow Protection in	Inbuilt hydrophobic and antibacterial filter		
Disposable Liner Canister Dimensions	Unit: 850 H x 460 W x 420 D mm Packed: 910 H x 500 W x 500 D mm		
Weight	Unit Weight: 17.5 kg Packed Weight: 23kg		
GMDN	63642		
Device Class	Class IIa		

ACCESSORIES / SPARES				
SUC84600100	Rail, Multipurpose, 5-Position	SUC81030042	Jar, Suction, Reusable, 2L, Complete	
SUC84600101	Hook, RH for Multipurpose Rail	SUC84600125	Jar, Suction, Reusable, 5L, Complete	
SUC84600102	Hook, LH for Multipurpose Rail	SUC81030007	Jar, Suction, Reusable, 2L, Jar Only	
SUC84600103	Cap, for Multipurpose Rail	SUC84600135	Jar, Suction, Reusable, 5L, Jar Only	
SUC84600110	DO110 Bracket, Ring for 2L Reusable Jar		Lid, Assembly with Shutoff Valve and Seal for 1L/2L Reusable Jar	
SUC84600111	Bracket, Ring for 5L Reusable Jar	SUC84600145	Lid, Assembly with Shutoff Valve and Seal for 5L Reusable Jar	
SUC84600112	Bracket, Ring for 2L/3L FLOVAC Jar	SUC81030009	Kit, Seal, Lid, 1L/2L Reusable Jar (Pack 2)	
SUC84600113	Bracket, Ring for Catheter Holder	SUC84600155	Seal, Lid for 5L Reusable Jar	
SUC84600114	Catheter Holder	SUC84600176	Filter, Hydrophobic/Antibacterial for HiFlo2	
SUC84600115	Foot Switch for HiFlo2 Max	SUC80297001	Kit, Yellow Suction Tubing (20 metre roll)	
SUC84600120	Jar, Trap, 220mL for Multipurpose Rail	SUC84500122	Kit, Disposable FLOVAC 2L Liner (Pack 50)	
		SUC84500123	Kit, Disposable FLOVAC 3L Liner (Pack 50)	

All specifications are subject to change without notice. Please check the exact specification when ordering.

Sponsor:

ICU Medical Australia Pty Ltd Unit U, 10 - 16 South St, NSW 2116, Australia Telephone 1300 438 652 +61 2 9466 5300 Email au_orders@icumed.com Web www.clements.net.au





