Welch Allyn

Green Series 600 Minor Procedure Light



Whiter, Brighter and Greener

3 LEDs







WelchAllyn

The GS 600 Minor Procedure Light features:

- Three LEDs that provide a whiter, brighter light than halogen
- Less energy consumption for reduced cost of ownership
- No bulb replacement for cost savings
- Wider head, designed specifically for demanding viewing conditions

- Uniform spot and superior brightness for minor procedures and exams in any healthcare environment
- Minimal heat dissipation
- Touchless controls with dimming features
- 5-year limited warranty





Welch Allyn

Green Series 600 Minor Procedure Light

ORDERING INFORMATION

44600 GS 600 Minor Procedure Light with

Mobile Stand

44610 GS 600 Minor Procedure Light with

Table/Wall Mount

52630 Disposable Sheath for GS 600/GS 900

(50/box, 5 boxes/case)

44215 12" Wall Mount Extension48960 Heavy Duty/Tall Mobile Stand



SPECIFICATIONS

Number of LEDs	3 White LEDs
Color Temperature	5,500° K
Light Intensity @ Typical Working Distance	High Intensity Setting: 12" distance: 75,000 lux (6,967 footcandles) 20" distance: 40,000 lux (3,716 footcandles) Low Intensity Setting: 12" distance: 55,000 lux (5,109 footcandles) 20" distance: 30,000 lux (2,787 footcandles)
LED Life	50,000 hours
Working Distance	12 in (30.5 cm) to 20 in (50 cm)
Spot Size at Working Distance	6 in (15 cm) to 7 in (18 cm)
Electrical	Input: 100-240 V~ 50 Hz-60 Hz, 0.65 A max
Power Cord	#18 AWG, 3-wire grounded cord set, 8' (2.5 m) long
Physical Dimensions	Weight: Total Table/Wall Mount: 6.45 lbs (2.93 kg) Total Mobile Stand: 17.35 lbs (7.87 kg) Control Box: Height: 10.83 in (27.5 cm) Width: 3.94 in (10.0 cm) Depth: 3.15 in (8.0 cm) Luminaire: Height: 13.58 in (34.5 cm) Width: 7.56 in (19.2 cm) Depth: 3.39 in (8.6 cm) Mobile Stand: Height: 24.02 in (61 cm) Diameter: 20.87 in (53 cm) Total Wall Mount: 33.27 in (84.5 cm) Total Mobile Stand: 58.66 in (149.0 cm) Table/Wall and Mobile Stand to Luminaire Center: 31.1 in (79 cm)
Mounting Options	Table/Wall Mount, Mobile Stand
Control Box	Touchless On/Off Control with Dimming
Accessory Options	Disposable Sheath #52630
Warranty	5-year limited

IDEAL FOR USE IN THE FOLLOWING ENVIRONMENTS:

- PRIMARY CARE CLINICS
- OUTPATIENT FACILITIES
- HOSPITAL—ER AND ICU
- OB/GYN
- DERMATOLOGY
- URGENT CARE CENTERS

MOUNTING OPTIONS AVAILABLE:







