

## Building Product Information

### Athena Acrylic Drop in Baths

---

**Version:** 1 : August 2023

#### Class 1

**Product Name** Liquid, Solace

**Product Line**

**Product Identifier** Baths

---

### Product Description

Athena Drop in Baths are suitable for residential and commercial applications. They are manufactured from thermoformed Sanitary grade Acrylic and reinforced with a fibreglass sandwich laminate. Drainage to the waste will be no less than a 1:50 gradient

- Available in white
- The Liquid & Solace baths measure 1675x750mm
- Baths can be supplied as a bath only or supplied fitted with a support frame.
- The baths can be factory fitted with 15mm Powder coated upstands on two or three sides
- It may also come as a full package which includes the bath, wall liner and bath swing
- Baths can be used as Shower over bath when an optional acrylic wall liner &, Bath Swing panel is specified

---

### Relevant Building Code Clauses

- B2 - Durability
  - E3 - Internal Moisture
  - G1 - Personal Hygiene
  - G12 - Water Supplies
-

## Contribution to Compliance

- E3/AS1 3.2.2– Baths may have a 15mm factory fitted upstand that an impervious wall liner can be sealed against preventing water penetration
- B2/AS1 - Durability: Athena baths with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
- Athena baths are designed to AS/NZS 2023-1995 Baths for Ablutionary Purposes
- G1.3.2—Avoids Harboursing dirt or germs
- G12.3.5 - Requires hot water for personal washing, showering or bathing

When used as a shower over bath the following additions apply

- E3/AS3.3.1.3 -Shower over baths
- E3/AS1 3.3.1.2- Shower wall linings
- F2 AS1 1.1.1- Human Impact

---

## Scope of Use

- Athena drop in baths are for internal installations only.

---

## Conditions of Use

- The bath's top perimeter flange must be installed level to ensure drainage.
- The bath's top perimeter and floor must be supported to prevent any deflection
- For safety reasons hot water temperature must be limited to 50 °C
- Any Plumbing must be carried out by a certified Plumber

---

## Additional Information

Installation information visit - <https://athena.co.nz/installation/installation-instructions/>

Warranty & Maintenance information visit - <https://athena.co.nz/athena-warranty/>

---

## Contact Details

<b>Manufacture Location</b>	New Zealand
<b>Legal and trading name</b>	OPR Ltd trading as Athena Bathrooms
<b>Address for service</b>	54-58 Hillside Rd, Glenfield, Auckland 0627
<b>Website</b>	<a href="https://athena.co.nz/">https://athena.co.nz/</a>
<b>Email</b>	<a href="mailto:info@athena.co.nz">info@athena.co.nz</a>
<b>Phone number</b>	(09) 443 9551
<b>Manufacturers NZBN</b>	9429038152573

---

## Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004