

Building Product Information

Motio Shower Set

Version: 1 : August 2023

Class 1

Product Name Motio

Product Line

Product Identifier Showers

Product Description

The Motio shower system is designed for new bathrooms or bathroom renovations.

The system consists of an acrylic shower tray, acrylic wall liner (optional), a semi frameless Sliding door set, Shower waste, sealants and adhesives.

The shower is designed as a complete shower fixture (less plumbing) that does not require a waterproof membrane.

Key technical specifications:

- Rectangular size* - 1200x900mm, and 1800x1000mm in 2 sided & alcove configurations
- Wall Liners are manufactured from single piece acrylic capped ABS at 2000mm tall.
- Door sets are 2000mm tall and use 8mm Grade A Safety glass
- Door set finishes - Bright anodised & optional Black upgrade
- Suitable for use with acrylic wall liners or with tiles up to 10mm.
- The 1200x900mm size tray has a 25mm upstand and has a corner back waste.
- The 1800x1000mm size tray has a 40mm upstand and has a centre back waste.
- The trays are supplied with an Athena 40mm Easyclean waste trap

* Other Motio door sets are available on their own in sizes of 1200x1000mm, 1400x1000mm & 1600x1000mm sided & alcove configurations

Relevant Building Code Clauses

- **E3/AS1 3.3.1**-Showers
 - **G1 AS1 2.6.1** - Sanitary Fixtures
 - **E3/AS1 3.3.1.2** - Shower wall lining and finish materials
 - **F2 AS1 1.1** - Human Safety Impact
 - **E3/AS1 3.3.2** - Shower Enclosures
 - **G13 /AS1 3.2.1** - Water Trap Dimensions
-

Contribution to Compliance

- B2/AS1 - Durability: Athena Showers with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
 - E3/AS1 3.3.1- Acrylic Wall linings are impervious to water
 - E3/AS1 3.3.1.2 - Athena Shower liners are made from a single piece of material without any joints and are continuous to a minimum height of 1920mm from tray level
 - E3/AS1 3.3.2.2 - When the acrylic wall lining is installed in conjunction with a Athena Shower Tray the junction is constructed in accordance with Fig 3 (E3/AS1)
 - F2/AS1 1.1.1- Human Impact Safety. All glass used in Athena Shower Enclosures meet AS/NZS 4223.3:2016 Glazing in Buildings Part 3 Human Safety Requirements.
 - G1/AS1 2.6.1 - Shower trays comply to AS 3588
 - G1.3.2 - Avoids Harboursing dirt or germs
 - G12.3.5 - Requires hot water for personal washing, showering or bathing
 - G13/AS1 3.2.1 - The Athena Easyclean waste trap has a water seal of 75mm
-

Scope of Use

- Motio showers are for internal installations only.
 - The shower set is suitable for residential and commercial applications
-

Conditions of Use

- If the Door set is to be installed on an Athena shower tray with tiled walls the Door set must be installed to the tile face
 - Only the Adhesives & Sealants supplied by the manufacturer must be used in the installation
 - Any Plumbing must be carried out by a certified Plumber
-

Additional Information

Installation information visit - <https://athena.co.nz/installation/installation-instructions/>

Warranty & Maintenance information visit - <https://athena.co.nz/athena-warranty/>

Building Product Information for the individual components visit - <https://athena.co.nz/bpir/>

Contact Details

Manufacture Location	New Zealand
Legal and trading name	OPR Ltd trading as Athena Bathrooms
Address for service	54-58 Hillside Rd, Glenfield, Auckland 0627
Website	info@athena.co.nz
Email	info@athena.co.nz
Phone number	(09) 443 9551
Manufacturers NZBN	9429038152573

Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004
