

# athena

## BATHROOMS

### Building Product Information

#### Soltero Vanity Series

---

**Version:** 1 : October 2023

**Class 1**

**Product Name** Wave Soltero, Cara Soltero, Nera Soltero, Menuet Soltero, Serifos Soltero

**Product Line**

**Product Identifier** Vanities

---

#### Product Description

The Soltero cabinet is constructed from low formaldehyde moisture resistant board finished with a low pressure laminate (melamine). The board is sourced from New Zealand's sustainable FSC certified Radiata pine plantations. Edges are taped with colour matching edge tapes bonded with PUR bonding technology providing a heat resistant, moisture resistant and near seamless bond

- Soltero cabinets are available to suit washbasin sizes of 610mm, 750mm, 810mm, 900mm, 1010mm,1200mm, 1500 sizes and benchtops of 750mm,800mm,900mm,1000mm,1200mm,1500mm
  - Available in a range of colours and finishes
  - Features Brushed Nickel handle with colour upgrades available
  - Features Soft close drawers
  - Depending on top design configurations may include Single Drawer and Double Drawer wall
- 

#### Relevant Building Code Clauses

- G1 - Personal Hygiene
  - B2 - Durability
  - G12 - Water Supplies
- 

#### Contribution to Compliance

- G1. 3.2- The Washbasins are impervious to water and stain resistant.
  - G1 AS1 - 2.6.1- AS/NZS 1730:1996-Washbasins
  - B2/AS1 - Durability: The Vanity with normal maintenance meets the Durability requirements of Nominated Building Elements for Plumbing & Pipe fixtures of not less than 5 years
  - G12.3.5 - Requires hot water for personal washing, showering or bathing
  - F2.3.1 - Athena vanities are constructed from low emission E1 standard board
-

## Scope of Use

- Athena vanities are for internal installations only.
  - They are suitable for use in Residential and Commercial applications.
- 

## Conditions of Use

- Vanity cabinets require walls to be plumb and flat.
  - While constructed from moisture resistant board it is recommended the room be well ventilated
  - Do not position the vanity cabinet in the direct path of any water, any spillages must be wiped up immediately
  - Cabinets must be installed level and without any twist for doors and drawers to operate
  - Cabinets must be attached to the walls using suitable hardware fixed into solid fixings such as studs or noggs
  - When installed, the cabinet must be sealed to the wall.
  - When installed, the bench top must be sealed to the wall and cabinet. Basins must be sealed to the bench top.
  - Any Plumbing must be carried out by a certified Plumber
- 

## Additional Information

Installation information visit - <https://athena.co.nz/installation/installation-instructions/>

Warranty & Maintenance information visit - <https://athena.co.nz/athena-warranty/>

---

## Contact Details

<b>Manufacture Location</b>	New Zealand
<b>Legal and trading name</b>	OPR Ltd trading as Athena Bathrooms
<b>Address for service</b>	54-58 Hillside Rd, Glenfield, Auckland 0627
<b>Website</b>	<a href="https://athena.co.nz/">https://athena.co.nz/</a>
<b>Email</b>	<a href="mailto:info@athena.co.nz">info@athena.co.nz</a>
<b>Phone number</b>	(09) 443 9551
<b>Manufacturers NZBN</b>	9429038152573

---

## Warnings and Bans

This building product is not subject to warning or ban under section 26 of the Building Act 2004

---