

VAL-1-CW-ANT-27-ELV-120

### DESCRIPTION

Vale optimises functionality through its multidirectional luminescence while diffusing soft ambient light.

### TYPE

Ceiling/Wall

### DIMENSIONS

- Luminaire: 102 x 8 x 23cm / 40" x 3.25" x 9"

### POWER OPTIONS NORTH AMERICA

- Coverplate
- Mounts to standard depth octagon box
- Remote power supply for multiple Vale arrangements


### POWER OPTIONS WORLD MARKET

- Surface mounted
- Remote power supply only

### TECHNICAL INFORMATION

- Input Voltage: 110–120V, 220–240V, 110–277V
- Lamping: Integral 10W 24V DC LED CRI 90+, 50,000 hours
- Lumens: 694 lumens delivered
- Power Supply: Phase dimming, 0-10V, DALI

### COLOUR TEMPERATURE OPTIONS



### DIM TO WARM



### CERTIFICATIONS



\* APPLICATION: DRY INDOOR LOCATION ONLY


### MATERIALS

- Aluminum
- Acrylic

### FRAME FINISHES



### LENS FINISH



SERIES	UNIT	TYPE	FINISH	CCT	PS	VOLTAGE IN
VAL	<input type="checkbox"/> 1	CW	<input type="checkbox"/> ANT (ANTHRACITE) <input type="checkbox"/> SIL (SILICA) <input type="checkbox"/> RST (RUST)	<input type="checkbox"/> 27 (2700K) <input type="checkbox"/> 30 (3000K) <input type="checkbox"/> 35 (3500K) <input type="checkbox"/> 41 (4100K) <input type="checkbox"/> DW (DIM TO WARM)	<input type="checkbox"/> ELV <input type="checkbox"/> 010 <input type="checkbox"/> DAL	<input type="checkbox"/> 120 <input type="checkbox"/> 230 <input type="checkbox"/> 277*

\*277 ONLY AVAILABLE WITH 010

# VALE – C/W

## CEILING/WALL

MANUFACTURED IN CANADA

CAINE HEINTZMAN / 2021

### POSSIBLE ORIENTATIONS

The Vale Ceiling/Wall suspends horizontally or vertically on the ceiling or wall.

