# 8 Star 3 Speed Pump

The 8 Star energy efficient pump with 3 speed control for maximum performance. Saves up to 70% of running costs compared to a single speed pump. Specifically designed to circulate swimming pool water for filtration, heating and sanitising applications. Suitable for pools up to 90,000 litres.

- 3 speed variable control with fully programmable speed options for maximum performance and efficiency
- See through lid for visibility and easy maintenance
- Extra large leaf basket for longer intervals between cleaning
- Advanced technology brushless DC motor for longer pump life
- Auto reset thermal protection to prevent over heating of the motor
- Strong corrosion resistant, UV stabilised materials
- 40/50mm ABS quick coupling barrel unions for easy connection and installation



### **Features**

#### > 3 Speed Control

Switch between Eco Flow (lowest speed) for pool filtration, Mid Flow for pool cleaning and High Flow for all other pool sanitisation and heating applications

#### > Programmable Intelligence

Fully programmable speed options by adjusting the RPM of the motor from the factory pre-sets for Eco, Mid and High Flow speeds. This maximises your pool efficiency, use and performance.

#### > Energy Efficient

Lower emissions, power usage and energy costs compared to single speed pumps

#### > Lower Noise Levels

Quiet at only 60.5dB, allowing you to run your pump at any time of day or night

## > 4 Year Guarantee

Peace of mind from an Australian owned, designed and engineered pool pump

Floatvical Data					
Electrical Data					
Model	H83SP				
	Eco Flow Speed – 1400				
RPM	Mid Flow Speed – 2400				
	High Flow Speed – 2850				
Enclosure Class (IP)	24				
Insulation Class	Class B130 Insulation				
Voltage (V)	220-240				
Supply Frequency (Hz)	50				
Run Current (A)	6.3				
	Eco Flow - 168W				
Motor Input Power (W)	Mid Flow – 679W				
	High Flow – 1125W				
	Eco Flow - 127W / 0.2 hp				
Motor Output Power (W / hp)	Mid Flow – 521W / 0.7 hp				
	High Flow – 853W / 1.1 hp				

Operating Limits						
Maximum water temperature	50°C					
Maximum ambient temperature	55°C					

Low Energy Operation: 3 speed settings which are also fully programmable:

- Eco Flow Lowest Speed
  Mid Flow Medium Speed
- 3. High Flow Highest Speed

Eco Flow mode provides the lowest speed and the greatest energy savings.



Operation	Recommended Speed Setting
Pool filtration	Eco Flow
Automatic pool cleaner operation	Mid Flow
Backwashing your media filter	
Manually cleaning your pool	
Water feature operation	High Flow
Spa jet operation	
Solar pool heating	

25 Total I	Head (m)						
20							
15			2850	rpm			
10							
5	1400rpm	2400rpm					
0 0	50 100	150 200	250	300	350 40	00 450	50

Dimensions (mm)								
А	В	С	D	Е	Mounting Holes Dia.	Inlet PVC	Outlet PVC	Net Weight (Kg)
645	330	250	305	246	10	40/50	40/50	15.9





