Valvoline, N

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ ENV C2 5W30

Product code : 872520

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains Molybdenum polysulphide long chain alkyl dithiocarbamate complex,

C14-16-18 Alkyl phenol. May produce an allergic reaction.

SynPower™ ENV C2 5W30



Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients


3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Long Chain Alkaryl Amine		Aquatic Chronic4; H413	>= 1,00 - < 2,50
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 1,00 - < 2,50
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 1,00 - < 2,50
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 1,00 - < 2,50
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	457-320-2 01-0000019337-66-xxxx	Skin Irrit.2; H315 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 0,25 - < 0,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 0,10 - < 0,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures





Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Protect unharmed eye.

Remove contact lenses.

If swallowed : If symptoms persist, call a physician.

Never give anything by mouth to an unconscious person.

Do not give milk or alcoholic beverages.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

: Hydrocarbons

products

carbon dioxide and carbon monoxide

Valvoline

SynPower™ ENV C2 5W30

Revision Date: 06.01.2020 Version: 4.0 Print Date: 06/11/2020

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

Valvoline,

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum polysulphide long chain alkyl dithiocarbamate complex		TWA	10 mg/m3	SUPLR EXP

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

Remarks : Nitrile rubber butyl-rubber

Skin and body protection : Safety shoes

Wear as appropriate:

Respiratory protection : No personal respiratory protective equipment normally

required.

Valvoline,

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : $<= -39 \, ^{\circ}\text{C}$

Boiling point/boiling range : No data available

Flash point : 232 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0,853

Density : ca. 0,851 g/cm3 (15,6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Valvoline_m

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 56 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : None known.

None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

SynPower™ ENV C2 5W30



Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: No mortality observed at this dose.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Components:

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Components:

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.



SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

Long Chain Alkaryl Amine:

Result: No skin irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No skin irritation

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No skin irritation

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Species: Rabbit

Result: Irritating to skin.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Long Chain Alkaryl Amine:

Result: No eye irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No eye irritation

HEAVY PARAFFINIC DISTILLATE:

SynPower™ ENV C2 5W30



Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Result: No eye irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No eye irritation

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Species: Rabbit

Result: Slight, transient irritation

C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1B.

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

LONG CHAIN ALKYL THIOCARBAMIDE METAL COMPLEX:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Valvoline...

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Result: negative

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Valvoline...

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Long Chain Alkaryl Amine Ecotoxicology Assessment

Long-term (chronic) aquatic : May cause long lasting harmful effects to aquatic life.

hazard

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOELR: >= 1.000 mg/l Exposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other

aquatic invertebrates

(Chronic toxicity)

NOEL: 10 mg/l

Exposure time: 21 d

Species: Daphnia (water flea)

Test substance: WAF

SynPower™ ENV C2 5W30



Revision Date: 06.01.2020 Version: 4.0 Print Date: 06/11/2020

Method: OECD Test Guideline 211

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10.000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC 10 mg/l

Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Species: Aquatic invertebrates

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 94,8 mg/l

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 50 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): 4,05

mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

(Chronic toxicity)

NOELR 100 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

SynPower™ ENV C2 5W30



Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

C14-16-18 Alkyl phenol

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

12.2 Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 23 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: Information given is based on data obtained from

similar substances.

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

12.3 Bioaccumulative potential

Components:

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Partition coefficient: n- : log Pow: > 5,1

octanol/water Method: OECD Test Guideline 107

C14-16-18 Alkyl phenol



SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

Partition coefficient: n-

octanol/water

: $\log Pow: > 7,2$

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good



SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

: Not applicable

deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic

Not applicable

pollutants

Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

: Not applicable

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Valvoline_{TM}

SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : Not On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information: 000000085235

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.



SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by

Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment



SynPower™ ENV C2 5W30

Version: 4.0 Revision Date: 06.01.2020 Print Date: 06/11/2020

STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class