



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ SAE 5W-40
Synthetic Motor Oil

Product code : 872380

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

2.3 Other hazards

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 25,00 - < 40,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate)	93819-94-4 298-577-9 01-2119543726-33-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical
advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get
medical attention.



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

- If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
- Risks : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
nitrogen oxides (NOx)
zinc oxide
Sulphur oxides
hydrogen sulfide
mercaptans

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Zinc bis[O-(6-methylheptyl)]	:	End Use: Workers
bis[O-(sec-butyl)]	:	Exposure routes: Inhalation
bis(dithiophosphate)	:	Potential health effects: Long-term systemic effects
	:	Value: 8,31 mg/m³RD TOX - Repeated dose toxicity
	:	End Use: Workers



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 0,58 mg/kgRD TOX - Repeated dose toxicity
End Use: Consumer use
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 2,11 mg/m3RD TOX - Repeated dose toxicity
End Use: Consumer use
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 0,29 mg/kgRD TOX - Repeated dose toxicity
End Use: Consumer use
Exposure routes: Oral
Potential health effects: Long-term systemic effects
Value: 0,24 mg/kgRD TOX - Repeated dose toxicity

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : Nitrile rubber butyl-rubber

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber



SAFETY DATA SHEET
SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Odour	:	oily
Odour Threshold	:	No data available
pH	:	Not applicable
Pour point	:	< -39,00 °C
Boiling point/boiling range	:	> 225,00 °C
Flash point	:	229 °C Method: ASTM D 92
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0,01 hPa (25 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0,853 (15,6 °C)
Density	:	0,855 g/cm ³ (15,6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 85 mm ² /s (40 °C)



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide and carbon monoxide
hydrogen sulfide
Nitrogen oxides (NO_x)
Sulphur oxides
zinc oxide fumes
mercaptans

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Acute toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5,58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5.000 mg/kg Remarks: No mortality observed at this dose.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: Information given is based on data obtained from similar substances.

Components:

ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity	: LD50 (Rat): 2.600 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 3.160 mg/kg Method: OECD Test Guideline 402 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.



SAFETY DATA SHEET
SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: **Rabbit**
Result: **No skin irritation**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: **Rabbit**
Result: **Mild skin irritation**
Remarks: **Information given is based on data obtained from similar substances.**

ZINC DIALKYLDITHIOPHOSPHATE:

Species: **Guinea pig**
Method: **OECD Test Guideline 404**
Result: **Irritating to skin.**
Remarks: **Information given is based on data obtained from similar substances.**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: **Rabbit**
Result: **No eye irritation**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: **Rabbit**
Result: **Slight, transient irritation**
Remarks: **Information given is based on data obtained from similar substances.**

ZINC DIALKYLDITHIOPHOSPHATE:

Species: **Rabbit**
Result: **Corrosive**
Remarks: **Information given is based on data obtained from similar substances.**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: **Buehler Test**
Species: **Guinea pig**
Assessment: **Does not cause skin sensitisation.**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: **Guinea pig**
Assessment: **Does not cause skin sensitisation.**
Method: **OECD Test Guideline 406**
Remarks: **Information given is based on data obtained from similar substances.**

Germ cell mutagenicity

Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

ZINC DIALKYL DITHIOPHOSPHATE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Method: **OECD Test Guideline 471**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

Genotoxicity in vivo : Test Type: **Micronucleus test**
Test species: **Mouse**
Method: **OECD Test Guideline 474**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

Carcinogenicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

	Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1.000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

bis(nonylphenyl)amine

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 5,4 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	: EC50 (Selenastrum capricornutum (green algae)): 2,1 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

12.2 Persistence and degradability

Components:



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **2 - 4 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

bis(nonylphenyl)amine

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **1,5 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

12.3 Bioaccumulative potential

Components:

bis(nonylphenyl)amine

Partition coefficient: n-octanol/water : log Pow: **> 7,5**

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Partition coefficient: n-octanol/water : log Pow: **0,59 - 1,2 (23 °C)**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 850/2004 on persistent organic : Not applicable



SAFETY DATA SHEET
SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

pollutants

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : R0517099

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :
ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index



SAFETY DATA SHEET

SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020

CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class



SAFETY DATA SHEET
SynPower™ SAE 5W-40 Synthetic Motor Oil

Version: 3.0

Revision Date: 03.04.2020

Print Date: 06/11/2020
