

linelube Agri UTTO 10W-40

Product Description

linelube Agri UTTO 10W-40 is a semi-synthetic universal tractor transmission oil formulated from premium quality semi-synthetic base oils, together with a special performance package and shear stable viscosity modifiers, providing an advanced lubricant which demonstrates excellent performance characteristics against the various stringent test requirements of major equipment manufacturers.

Features & Benefits

- Superior oxidation stability
- Outstanding rust and corrosion protection
- Excellent wet brake, anti-squawk and chatter suppression
- Exceptional anti-wear and extreme pressure properties
- Excellent high and low temperature performance
- Low foaming tendency and good seal compatibility

Applications

linelube Agri UTTO 10W-40 is suitable for use in hydraulic – transmission fluid, specifically designed for use in agricultural tractor power transmission – hydraulic systems, inboard wet brakes and rear axles, employed in the majority of modern farm tractors, agricultural machinery and some construction equipment.

Specifications

- Allison C-4
- Kubota UDT Fluid
- Valtra G2-08
- Caterpillar T0-2
- John Deere JDM J20C, J20D
- Ford ESN-M2C86B 86C, M2C-134D
- Case MS 1210
- Case New Holland CNH MAT3505, 3509, 3525
- ZE TE-ML 03E, 05F, 06K, 17E, 21F VCE WB101
- Agco Powerfluid 821XL
- Massey Ferguson MF CMS 1135, 1141, 1143, 1145

Typical Test Data

| | |
|------------------------------|-------|
| Kinematic Viscosity: @ 40°C | 40.5 |
| Kinematic Viscosity: @ 100°C | 7.7 |
| Viscosity Index | 165 |
| Closed Flash Point (°C) | 195 |
| Pour Point (°C) | 42 |
| Density @ 15°C | 0.887 |

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet are given in good faith but without warranty.