

linelube Synthetic 5W-40 Engine Oil

Product Description

linelube Synthetic 5W-40 is a fuel-efficient multi-grade engine oil meeting current API classification. The demand for synthetic lubricants has increased dramatically over a short period of time. Many engine manufacturers have recognised the benefits when using a synthetic product. Synthetic 5W-40 is manufactured from fully synthetic base stocks and additive technology available, providing a lubricant which delivers outstanding performance and durability for the most demanding motorist. It offers quicker oil circulation, far improved cold starting properties and higher lubricity, for reduced internal friction than standard mineral based engine oils.

Features & Benefits

- Effective environmental protection
- Ensures lubricant performance over extended drain intervals
- Effective fuel efficiency
- Very high standards of engine cleanliness
- Exceptional long term antiwear and oxidation stability
- Excellent high and low temperature performance
- Exceptional long-term additive response

Applications

Synthetic 5W-40 is suitable for normally aspirated and turbo charged petrol engines and diesel engines. For passenger cars and light commercials and is suitable for all driving conditions. It is miscible with all synthetic and mineral based engine oils.

Specifications

- **API:** SL/CF
- **ACEA:** A3, B3, B4
- **VW:** 502.00, 505.00
- **MB:** 229.1, 229.3

Typical Test Data

Specific Gravity @ 15.6°C	0.849
Kinematic Viscosity @ 40°C	93.05
Kinematic Viscosity @ 100°C	14.73
Viscosity Index	166
Pour Point (°C)	-40
Flash Point (°C)	223
Total Base Number (mg KOH/g)	10.4

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.