

Linelube OW-30 C3 Fully Synthetic Engine Oil

Product Description

A fully synthetic mid SAPS automotive engine oil.

Features & Benefits

- Advanced anti-wear technology helps to protect engine components.
- Compatible with Diesel particulate filters (DPF) and three-way catalysts (TWC).
- Engineered to have good oxidation resistance, thermal stability and superb low temperature performance.
- High standards of engine cleanliness.
- Increased performance and fuel efficiency.
- Offers extended service intervals.

Applications

A fully synthetic mid SAPS engine oil formulated for use with modern petrol and diesel engines. Specialist Adaptive Molecular Technology maintains the power and efficiency of engines to improve overall reliability whilst ensuring optimum performance and supporting exhaust aftertreatment devices throughout the vehicle's lifecycle.

Specifications

- **ACEA** C3
- API SN/CF
- **BMW** LL-04
- GM Dexos 2
- Mercedes-Benz 229.51/229.52
- VW 502.00/505.01

Typical Test Data

Density @ 15°C (kg/m3)	ASTM D4052	0.843
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	53
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	9.5
Viscosity Index	ASTM D2207	165
Pour Point (°C)	ASTM D97	-50
Flash Point (°C)	ASTM D92	212
Total Base Number (mg KOH/g)	ASTM D2896	8

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.

www.linelube.co.uk

Last update: 03/05/2022