

Linelube SHPD 15W-40 E7

Product Description

Heavy-duty diesel engine oil.

Features & Benefits

- Anti-wear performance for reduced engine wear.
- High shear stability for stay in grade performance.
- High thermal stability provides protection against piston deposits.
- Ideal mixed fleet lubricant.
- Improved bore polishing protection.
- Powerful detergent & dispersant technology.

Applications

A heavy-duty diesel engine oil formulated to meet the most severe of lubrication requirements. A blend of solvent refined base oils, viscosity index improvers, pour point depressants and an innovative additive system that is designed to provide effortless performance.

Specifications

Manufacturer Approvals:

- Mack EO-N
- Renault RLD-2
- Volvo VDS-3

Recommended as suitable for the following applications:

- ACEA E7, E5, E3
- API CI-4, CH-4
- Cummins 20078, 20077, 20076, 20072
- Caterpillar ECF-2, ECF-1a
- Deutz DQC III-10
- Global DHD
- JASO DH-1
- MAN M3275
- Mercedes-Benz 228.3
- MTU Type 2
- ZF TE ML 07C

Suitable for DAF, Scania & Perkins

Typical Test Data

Density @ 15°C	ASTM D4052	0.887
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	106
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	14.4
Viscosity Index	ASTM D2207	139
Pour Point (°C)	ASTM D97	-31
Flash Point (°C)	ASTM D92	210
Total Base Number (mg KOH/g)	ASTM D2896	11

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.