


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

Trade name : SynPower™ FE SAE 5W30
Synthetic Motor Oil

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements
Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

2.3 Other hazards
Additional advice

No information available.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

SECTION 3: Composition/information on ingredients
3.2 Mixtures
Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 80,00 - < 90,00
Reaction products of Benzeneamine, N- phenyl- with nonene (branched)	36878-20-3 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate)	93819-94-4 298-577-9 01-2119543726-33-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
- Risks : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures
5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
nitrogen oxides (NO_x)
zinc oxide
Sulphur oxides
hydrogen sulfide


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 00000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

mercaptans

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls
Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 00000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

pH	:	Not applicable
Pour point	:	< -39,00 °C
Boiling point/boiling range	:	> 225,00 °C
Flash point	:	209 °C
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	25 hPa Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	ca. 0,852
Density	:	ca. 0,852 g/cm ³ (15 °C)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 9,8 mm ² /s (100 °C) ca. 54 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

No data available


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materialsMaterials to avoid : Strong bases
Strong oxidizing agents**10.6 Hazardous decomposition products**Hazardous decomposition products : carbon dioxide and carbon monoxide
hydrogen sulfide
Nitrogen oxides (NO_x)
Sulphur oxides
zinc oxide fumes
mercaptans

SECTION 11: Toxicological information
11.1 Information on toxicological effectsInformation on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion**Acute toxicity**

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation under GHS.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

Components:

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Acute oral toxicity : LD50 (Rat): 2.600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Components:

C14-16-18 Alkyl phenol

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by ingestion under GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Species: Rabbit

Result: No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Rabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 00000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Species: Guinea pig

Method: OECD Test Guideline 404

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Method: OECD Test Guideline 431

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Species: Rabbit

Result: No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Species: Rabbit

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo : Test Type: Micronucleus test
 Test species: Mouse
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure


Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol

		Page: 11
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
SynPower™ FE SAE 5W30 Synthetic Motor Oil		SDS Number: 000000098054
872551		Version: 2.2

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
 May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10.000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: Calculated >= 1.000 mg/l
 Exposure time: 14 d
 Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates : NOEL: 10 mg/l
 Exposure time: 21 d


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 06.11.2020

SDS Number: 000000098054

SynPower™ FE SAE 5W30 Synthetic Motor Oil

Version: 2.2

872551

(Chronic toxicity)

Species: Daphnia (water flea)
 Test substance: WAF
 Method: OECD Test Guideline 211

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l
 Exposure time: 96 h
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 5,4 mg/l
 Exposure time: 48 h
 Test Type: static test


Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 2,1 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test

C14-16-18 Alkyl phenol

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test

		Page: 13
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
SynPower™ FE SAE 5W30 Synthetic Motor Oil		SDS Number: 000000098054
872551		Version: 2.2

Test substance: WAF

12.2 Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 0 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 1,5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.
 Remarks: Expert judgement

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Partition coefficient: n-octanol/water : log Pow: > 7,5

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Partition coefficient: n-octanol/water : log Pow: 0,59 - 1,2 (23 °C)

C14-16-18 Alkyl phenol


Partition coefficient: n-octanol/water : log Pow: > 7,2

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

		Page: 14
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
SynPower™ FE SAE 5W30 Synthetic Motor Oil		SDS Number: 000000098054
872551		Version: 2.2

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

SECTION 14: Transport information

14.1 UN number

ADN: Not dangerous goods
ADR: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods
INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods
RID: Not dangerous goods

14.2 UN proper shipping name


ADN: Not dangerous goods
ADR: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods
INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods
RID: Not dangerous goods

14.3 Transport hazard class(es)

ADN: Not dangerous goods
ADR: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods
INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods
RID: Not dangerous goods

14.4 Packing group

ADN: Not dangerous goods
ADR: Not dangerous goods

		Page: 15
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
		SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil		Version: 2.2
872551		

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods
INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods
RID: Not dangerous goods

14.5 Environmental hazards

ADN: Not applicable
ADR: Not applicable
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not applicable
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not applicable
INTERNATIONAL MARITIME DANGEROUS GOODS: Not applicable
RID: Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code


Ship Type: Not applicable
Hazard code(s): Not applicable
Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

		Page: 16
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
		SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil		Version: 2.2
872551		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL All components of this product are on the Canadian DSL
- AICS On the inventory, or in compliance with the inventory
- ENCS Not in compliance with the inventory
- KECI On the inventory, or in compliance with the inventory
- PICCS On the inventory, or in compliance with the inventory
- IECSC On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available


SECTION 16: Other information

Further information

Revision Date: 11.01.2017

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318** Causes serious eye damage.
- H373** May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H413** May cause long lasting harmful effects to aquatic life.


		Page: 17
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 06.11.2020
SynPower™ FE SAE 5W30 Synthetic Motor Oil		SDS Number: 000000098054
872551		Version: 2.2

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

	Page: 18
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 06.11.2020
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging
 CSA : Chemical Safety Assessment
 CSR : Chemical Safety Report
 DNEL : Derived No Effect Level.
 EINECS : European Inventory of Existing Commercial Chemical Substances.
 ELINCS : European List of Notified Chemical Substances
 PEC : Predicted Effect Concentration
 PEL : Permissible Exposure Limits
 PNEC : Predicted No Effect Concentration
 R-phrase : Risk phrase
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
 S-phrase: Safety phrase
 WGK : German Water Hazard Class