according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : PURITY TM/MC FG2 SYNTHETIC

Product code : PFGSYN2P17, PFGSYN2KGL, PFGSYN2DRL, PFGSYN2,

PFGSYN2C30

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Purity FG2 Synthetic grease is a food grade lubricant.

stance/Mixture

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added

directly to the food product.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way

Birmingham International Park Solihull B37 7HB

United Kingdom

E-mail address of person

responsible for the SDS

: EUSDS@petrocanadalsp.com

#### 1.4 Emergency telephone number

Emergency telephone number : Petro-Canada Lubricants Inc.: +1 905-403-5770;

CHEMTREC Transport Emergency: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### **Additional Labelling:**

EUH208 May produce an allergic reaction.

Internet: lubricants.petro-canada.com/sds

Page: 1 / 10

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

EUH210 Safety data sheet available on request.

Contains: Sulfonic acids, petroleum, calcium salts and Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts and Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts and calcium dodecylbenzenesulphonate

#### 2.3 Other hazards

None known.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Sulfonic acids, petroleum, calcium	61789-86-4	Skin Sens. 1B; H317	1 - < 10
salts	263-093-9		
Benzenesulfonic acid, C10-16-	68584-23-6	Skin Sens. 1B; H317	1 - < 10
alkyl derivs., calcium salts	271-529-4		
Benzenesulfonic acid, mono-C16-	70024-69-0	Skin Sens. 1B; H317	1 - < 10
24-alkyl derivs., calcium salts	274-263-7		
calcium dodecylbenzenesulpho-	26264-06-2	Skin irr/cor. 2; H315	1 - < 2.5
nate	247-557-8	Eye irr/damage 1;	
		H318	
Benzenamine, N-phenyl-, reaction	68411-46-1	Aquatic Chronic 3;	1 - < 2.5
products with 2,4,4-	270-128-1	H412	
trimethylpentene			

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

Internet: lubricants.petro-canada.com/sds

Page: 2 / 10

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC

# PETRO-CANADA

#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

4.3 Indication of any immediate medical attention and special treatment needed

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion prod: :

ucts

Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the envi-

ronment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.

Internet: lubricants.petro-canada.com/sds

TM Owned or used under license.

Page: 3 / 10

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against

fire and explosion

None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use. Wash face, hands and any ex-

posed skin thoroughly after handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.

#### 7.3 Specific end use(s)

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### 8.2 Exposure controls

#### **Engineering measures**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Internet: lubricants.petro-canada.com/sds

Page: 4 / 10

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : Semi-solid.

Colour : cream

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -63 °C (-81 °F)

Base Fluid Blend

Boiling point/boiling range

No data available

Flash point : 252 °C (486 °F)

Method: Cleveland open cup

Base Fluid Blend

Fire Point : 286 °C (547 °F)

Base Fluid Blend

Auto-Ignition Temperature : No data available Evaporation rate : No data available

Flammability (solid, gas) : Low fire hazard. This material must be heated before ignition

will occur.

Internet: lubricants.petro-canada.com/sds

Page: 5 / 10

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available
Relative vapour density : No data available
Relative density : No data available

Density : 0.9568 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 50.0 cSt (40 °C / 104 °F)

Base Fluid Blend

7.80 cSt (100 °C / 212 °F)

Base Fluid Blend

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

#### 9.2 Other information

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

#### 10.2 Chemical stability

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents.

#### 10.6 Hazardous decomposition products

Hazardous decomposition

products

May release COx, SOx, CaOx, smoke and irritating vapours

when heated to decomposition.

Page: 6 / 10

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Print Date 2019/02/05 Version 2.3 Revision Date 2019/02/05

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Information on likely routes of:

exposure

Eye contact Ingestion Inhalation Skin contact

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: No data available

: Remarks: No data available Acute inhalation toxicity

: Remarks: No data available Acute dermal toxicity

Skin corrosion/irritation

**Product:** 

Remarks No data available

#### Serious eye damage/eye irritation

**Product:** 

Remarks : No data available

Remarks : No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

# STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

Internet: lubricants.petro-canada.com/sds

Page: 7 / 10

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: No data available

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms Remarks: No data available

#### 12.2 Persistence and degradability

Product:

: Remarks: No data available Biodegradability

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

Not relevant

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

# **SECTION 14: Transport information**

# **International Regulations**

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Internet: lubricants.petro-canada.com/sds TM Owned or used under license.

Page: 8 / 10

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



Page: 9 / 10

#### 000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

Remarks : ADR: Not Regulated

ADN: Not Regulated RID: Not Regulated

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

: WGK 2 water endangering

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EINECS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

AICS : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

: HSNO: HSR002605, Lubricants (Low Hazard) Group Stand-

ard 2017

#### 15.2 Chemical safety assessment

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity

Eye irr/damage : Serious eye damage/eye irritation

Skin Sens. : Skin sensitisation
Skin irr/cor. : Skin corrosion/irritation

Internet: lubricants.petro-canada.com/sds

TM Owned or used under license.

according to Regulation (EC) No. 1907/2006

# PURITY TM/MC FG2 SYNTHETIC



Page: 10 / 10

000003001183

Version 2.3 Revision Date 2019/02/05 Print Date 2019/02/05

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Europe, telephone: 00-800-7387-6000

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN

Internet: lubricants.petro-canada.com/sds

TM Owned or used under license.